

J1 HARNESS		J2 PROGRAMMER		J3 CAN ADAPTER		J4 DEVICE							
								WIRE					
DEUTSCH	UTSCH DT04-12PC-B016		DEUTSCH DT06-12SA-P012		DEUTSCH DT04-3P		DEUTSCH DT06-12SC-P012		ID	TWISTED PAIRS*	COLOR	AWG	LENGTH (INCH)
PII	N #	CODE	PIN #	CODE	PIN #	CODE	PIN #	CODE		-			·/
	1	T	1	J					GND	D	BLACK	18	14 3/4
1	1	Т	2	J					CAN LO IN	Α	GREEN	18	14 3/4
			3	J			1	J	GND	E	BLACK	18	14 3/4
			4	J			11	J	CAN LO OUT	В	GREEN	18	14 3/4
			5	J	С	T			GND		BLACK	18	14
			6	J	В	T			CAN LO PROG	С	GREEN	18	14 3/4
			7	J	Α	T			CAN HI PROG	С	YELLOW	18	14 3/4
			8						NC				
			9	J			2	J	CAN HI OUT	В	YELLOW	18	14 3/4
			10	J			12	J	POWER OUT	Е	RED	18	14 3/4
	2	T	11	J					CAN HI IN	Α	YELLOW	18	14 3/4
1	2	T	12	J					POWER IN	D	RED	18	14 3/4
W12P		W12S-P012		W3P		W12S-P012		WEDGE LOCK					
0413-217-1605		0413-217-1605		0413-217-1605		0413-217-1605		PLUG					

PIN CODE	PART #	TOTAL
J	0462-201-16141	15
T	0460-202-16141	7



Dimensions are approximate. For representation only.
Tolerances except where otherwise stated .X = +/-0.25

All data and drawing are sent without acknowledgement of a legal obligation, without guarantee of completeness and without promise of warranty. The data provided were ascertained using extreem care. However, possible sources of error cannot be excluded completely. We therefore do not accept any responsibility for damage and costs that may result from the use of these data. Binding data are to be taken exclusively from our drawings that are subject to confirmation. These contents are cofidential and property of 621 inc., so it must not be copied or submitted to third parties for use or examination.

DO NOT SCALE DRAWING

REVISION 1.0

621 Technologies inc.

SCALE : NONE

FLASH ADAPTER CABLE-**AXLETECH SELECTOR**

AATTC-001-H3

DIMENSIONS ARE IN INCHES UNLESS UNTIL SPECIFIED SHEET 2 OF 2

*IF APPLICABLE TWISTING SHOULD NOT BE LESS THAN ONE TWIST PER INCH UNLESS OTHERWISE SPECIFIED

\\Network\192.168.3.100\home